Flexible Barrier POLYGUARD PUFFyGuard

1R DELTA RACK END BARRIER

DESIGNED FOR EASY ASSEMBLY, THIS BARRIER IS PERFECT FOR REDUCING DAMAGE TO RACK LEGS IN STORAGE AREAS WITH TRANSPORT AND LOADING VEHICLE TRAFFIC. SPECIFICALLY ENGINEERED TO PROTECT RACK LEGS FROM CONSTANT IMPACTS, IT MINIMIZES WEAR AND TEAR CAUSED BY TRANSPORT AND STACKING VEHICLES, ENSURING LONG—TERM DURABILITY AND SAFETY. ITS ROBUST CONSTRUCTION HELPS MAINTAIN THE INTEGRITY OF STORAGE SYSTEMS, REDUCING REPAIR COSTS AND OPERATIONAL DISRUPTIONS.

RAYSAN

STRONG AND LIGHTWEIGHT

Thanks to its unique chemical formula, our barrier surpasses steel barriers in both strength and weight. It is significantly lighter while maintaining its exceptional durability.

MODULAR

Thanks to its modular design, our barrier effortlessly adapts to the changing needs of your facility. This flexible solution is extremely easy to install, assemble, disassemble, relocate and organize.

NO CORROSION

Unlike steel barriers, our barriers are made of durable polymer materials, making them unaffected by environmental elements such as sunlight and rainwater.

NO PAINT AND MAINTENANCE NEEDED

Unlike Raysan's steel barriers that require regular painting and maintenance, our self-colored structure eliminates the need for these processes. Even if the barrier is scratched due to an impact, its surface retains its original color without any change.

ULTRAVIOLET RESISTANT

Our barriers are designed with exceptional resistance to UV radiation. Their chemical structure remains intact even after prolonged outdoor use, ensuring long-term durability.


ANTIBACTERIAL

Our barriers have an exceptional chemical formula that prevents them from having any chemical reaction with the substances they come into contact with.

EXPERIENCE UNPARALLELED STRENGTH

WITH OUR ADVANCED POLYMER, CRAFTED
FROM A PREMIUM BLEND OF SOPHISTICATED
POLYOLEFINS AND RUBBER ADDITIVES. THIS
EXCLUSIVE COMPOSITION DELIVERS UNMATCHED
DURABILITY AND FLEXIBILITY. OUR CUTTING-EDGE
ENGINEERING PROCESS REORIENTS THE MOLECULAR
STRUCTURE DURING MANUFACTURING, ENDOWING THE
BARRIER WITH A UNIQUE BUILT-IN MEMORY. THIS
INNOVATIVE FEATURE ENSURES THAT THE BARRIER
RECOVERS COMPLETELY AFTER IMPACTS, MAINTAINING
PEAK PERFORMANCE AND RELIABILITY.





DELTA

Post Dimension [D1]

Ø200 mm

Post Height [H]

Rail Dimension [D2]

450 mm

100x100 mm



Rail Length Range [L1]

Barrier Length MAX [L2]


Impact Zone [Z]

800 mm - 2650 mm

2850 mm

100 mm

IMPACT DETAILS ENERGY



FIXING REQUIREMENTS



ELECTROSTATIC PAINT



STAINLESS STEEL



工

GALVANIZE



Concrete Quality	Minimum C25/30
Concrete Floor Plate Thickness [mm]	Minimum 150 mm
Water and Humidity	Steel [standart] : Suitable for dry indoor use only. Galvanize : Can be used in most outdoor environments. Stainless Steel : Ideal for outdoor use or environments with frequent exposure to water and humidity.



BUILDING AND

WAREHOUSE PROTECTION SOLUTIONS









SUITABLE **APPLICATION**

> *90° Impact on Mid Rail of Maximum Post Centres *Results are Reflecting instantaneous Impact Values *Does not Provide Resistance to Sharp Impacts

STANDART COLORS

_ D1_

TECHNICAL DRAWING


RAL 1018 PANTONE 123C

RAL 9005 PANTONE B6C

D2

L2

*Please note that the RAL and PANTONE colours listed are the closest match to standard RAYSAN colours, but may not be exact matches of the actual product colour and should be used for guidance only.



RAYSAN

AS RAYSAN, WE ARE PROUD TO PIONEER THE FUTURE OF INDUSTRIAL SAFETY. WITH OUR STATE—OF—THE—ART FLEXIBLE PROTECTIVE BARRIERS AND SOLUTIONS, WE ARE AT THE FOREFRONT OF INNOVATION, PROTECTING WORKPLACES AROUND THE WORLD. OUR COMMITMENT TO EXCELLENCE AND UNWAVERING DEDICATION TO ADVANCING SAFETY STANDARDS HAS PROPELLED US TO THE TOP OF THE INDUSTRY.

