Flexible Barrier POLYGUARD PUFFyGuard

O SR BARRIER

WITH ITS EASY—TO—ASSEMBLE DESIGN, THIS BARRIER IS PERFECT FOR PROTECTING STRUCTURES, GOODS, AND MACHINERY FROM HIGH—LEVEL VEHICLE IMPACTS IN INDOOR AND OUTDOOR AREAS WITH CARRYING AND LOADING TRAFFIC. IDEAL FOR PARKS, RAMPS, AND OPEN EDGES, IT ALSO DEFINES AND ORGANIZES SPACES WHILE ENSURING LASTING DURABILITY. BUILT TO WITHSTAND CONTINUOUS IMPACTS, IT MINIMIZES MAINTENANCE NEEDS, SAVING BOTH TIME AND COSTS.

STRONG AND LIGHTWEIGHT

Thanks to its unique chemical formula, our barrier surpasses steel barriers in both strength and weight. It is significantly lighter while maintaining its exceptional durability.

MODULAR

Thanks to its modular design, our barrier effortlessly adapts to the changing needs of your facility. This flexible solution is extremely easy to install, assemble, disassemble, relocate and organize.

NO CORROSION

Unlike steel barriers, our barriers are made of durable polymer materials, making them unaffected by environmental elements such as sunlight and rainwater.

NO PAINT AND MAINTENANCE NEEDED

Unlike Raysan's steel barriers that require regular painting and maintenance, our self-colored structure eliminates the need for these processes. Even if the barrier is scratched due to an impact, its surface retains its original color without any change.

ULTRAVIOLET RESISTANT


Our barriers are designed with exceptional resistance to UV radiation. Their chemical structure remains intact even after prolonged outdoor use, ensuring long-term durability.

ANTIBACTERIAL

Our barriers have an exceptional chemical formula that prevents them from having any chemical reaction with the substances they come into contact with.

EXPERIENCE UNPARALLELED STRENGTH

WITH OUR ADVANCED POLYMER, CRAFTED
FROM A PREMIUM BLEND OF SOPHISTICATED
POLYOLEFINS AND RUBBER ADDITIVES. THIS
EXCLUSIVE COMPOSITION DELIVERS UNMATCHED
DURABILITY AND FLEXIBILITY. OUR CUTTING-EDGE
ENGINEERING PROCESS REORIENTS THE MOLECULAR
STRUCTURE DURING MANUFACTURING, ENDOWING THE
BARRIER WITH A UNIQUE BUILT-IN MEMORY. THIS
INNOVATIVE FEATURE ENSURES THAT THE BARRIER
RECOVERS COMPLETELY AFTER IMPACTS, MAINTAINING
PEAK PERFORMANCE AND RELIABILITY.



DELTA

Post Dimension [D1]

Post Height [H]

Rail Dimension D2

Rail Length Range [L1]

Barrier Length MAX [L2]

Impact Zone [Z]

Ø200 mm

1100 mm

Ø160 mm

400 mm - 2700 mm

2900 mm

780 mm

ZETA

Post Dimension D1

Ø160 mm

Post Height [H]

1100 mm

Rail Dimension [D2]

Ø125 mm

Rail Length Range [L1]

Barrier Length MAX [L2]

Impact Zone [Z]


320 mm - 2350 mm

2510 mm

775 mm

FORCE

GROUND



FIXING REQUIREMENTS



ELECTROSTATIC PAINT



STAINLESS STEEL



GALVANIZE

Concrete Quality	Minimum C25/30
Concrete Floor Plate Thickness [mm]	Minimum 150 mm
Water and Humidity	Steel [standart]: Suitable for dry indoor use only. Galvanize: Can be used in most outdoor environments. Stainless Steel: Ideal for outdoor use or environments with frequent exposure to water and humidity.








BUILDING AND CORRIDOR AND WALL DEFENSES

PROTECTION SOLUTIONS
















*90° Impact on Mid Rail of Maximum Post Centres *Results are Reflecting instantaneous Impact Values *Does not Provide Resistance to Sharp Impacts

STANDART COLORS

RAL 1018 PANTONE 123C

RAL 9005 PANTONE B6C

are the closest match to standard RAYSAN colours, but may not be exact matches of the actual product colour and should be used for guidance only.



RAYSAN

AS RAYSAN, WE ARE PROUD TO PIONEER THE FUTURE OF INDUSTRIAL SAFETY. WITH OUR STATE—OF—THE—ART FLEXIBLE PROTECTIVE BARRIERS AND SOLUTIONS, WE ARE AT THE FOREFRONT OF INNOVATION, PROTECTING WORKPLACES AROUND THE WORLD. OUR COMMITMENT TO EXCELLENCE AND UNWAVERING DEDICATION TO ADVANCING SAFETY STANDARDS HAS PROPELLED US TO THE TOP OF THE INDUSTRY.

