Flexible Barrier POLYGUARD PUFFyGuard

2R BARRIER + KERB

WITH ITS EASY-TO-ASSEMBLE DESIGN, THIS BARRIER IS PERFECT FOR SAFEGUARDING STRUCTURES, GOODS, AND MACHINERY FROM MEDIUM-HEIGHT VEHICLE IMPACTS IN BUSY INDOOR AND OUTDOOR AREAS. REINFORCED WITH A KERB BARRIER, IT ALSO ORGANIZES AND DEFINES SPACES WHILE OFFERING EXTRA PROTECTION AGAINST COLLISIONS FROM FORKLIFT FORKS AND KNIVES WITH ITS ADDED RESTRICTIVE TYPE PROTECTION BARRIER.

RAYSAN

STRONG AND LIGHTWEIGHT

Thanks to its unique chemical formula, our barrier surpasses steel barriers in both strength and weight. It is significantly lighter while maintaining its exceptional durability.

MODULAR

Thanks to its modular design, our barrier effortlessly adapts to the changing needs of your facility. This flexible solution is extremely easy to install, assemble, disassemble, relocate and organize.

CORROSION-FREE

Unlike steel barriers, our barriers are made of durable polymer materials, making them unaffected by environmental elements such as sunlight and rainwater.

NO PAINTING OR MAINTENANCE REQUIRED

Unlike Raysan's steel barriers that require regular painting and maintenance, our self-colored structure eliminates the need for these processes. Even if the barrier is scratched due to an impact, its surface retains its original color without any change.

UV-RESISTANT

Our barriers are designed with exceptional resistance to UV radiation. Their chemical structure remains intact even after prolonged outdoor use, ensuring long-term durability.

ANTIMICROBIAL

Our barriers have an exceptional chemical formula that prevents them from having any chemical reaction with the substances they come into contact with.

EXPERIENCE UNPARALLELED STRENGTH

WITH OUR ADVANCED POLYMER, CRAFTED
FROM A PREMIUM BLEND OF SOPHISTICATED
POLYOLEFINS AND RUBBER ADDITIVES. THIS
EXCLUSIVE COMPOSITION DELIVERS UNMATCHED
DURABILITY AND FLEXIBILITY. OUR CUTTING-EDGE
ENGINEERING PROCESS REORIENTS THE MOLECULAR
STRUCTURE DURING MANUFACTURING, ENDOWING THE
BARRIER WITH A UNIQUE BUILT-IN MEMORY. THIS
INNOVATIVE FEATURE ENSURES THAT THE BARRIER
RECOVERS COMPLETELY AFTER IMPACTS, MAINTAINING
PEAK PERFORMANCE AND RELIABILITY.



ALPHA

Post Dimension [D1]

Ø95/6"

Post Height [H]

321/3"

Rail Dimension [D2]

Rail Length Range [L1]

Barrier Length MAX [L2]

Impact Zone Z

Ø75/6"

19¾" - 118"

128"

213/3"

DELTA

Post Dimension [D1]

Ø75/6"

Post Height [H]

29"

Rail Dimension [D2]

Ø61/3"

Rail Length Range [L1]

Barrier Length MAX [L2]

Impact Zone [Z]

15¾" - 106⅓"

1141/6"

181/2"



Post Dimension D1

Ø61/3"

Post Height [H]

263/8"

Rail Dimension [D2]

Ø5"

Rail Length Range [L1]

123/5" - 921/2"

Barrier Length MAX [L2]

98%"


153/4"

Impact Zone [Z]

PULL OUT

FORCE

GROUND



FIXING REQUIREMENTS




ELECTROSTATIC PAINT



STAINLESS STEEL



GALVANIZED








BUILDING AND CORRIDOR

MACHINERY PROTECTION SOLUTIONS
















*90° Impact on Mid Rail of Maximum Post Centres *Results are Reflecting instantaneous Impact Values *Does not Provide Resistance to Sharp Impacts

STANDART COLORS RAL 1018 PANTONE 123C

RAL 9005 PANTONE B6C

*Please note that the RAL and PANTONE colours listed are the closest match to standard RAYSAN colours, but may not be exact matches of the actual product colour and should be used for guidance only.

AND WALL



RAYSAN

AS RAYSAN, WE ARE PROUD TO PIONEER THE FUTURE OF INDUSTRIAL SAFETY. WITH OUR STATE—OF—THE—ART FLEXIBLE PROTECTIVE BARRIERS AND SOLUTIONS, WE ARE AT THE FOREFRONT OF INNOVATION, PROTECTING WORKPLACES AROUND THE WORLD. OUR COMMITMENT TO EXCELLENCE AND UNWAVERING DEDICATION TO ADVANCING SAFETY STANDARDS HAS PROPELLED US TO THE TOP OF THE INDUSTRY.

