Flexible Barrier POLYGUARD PuffyGuard

2R DELTA RACK END BARRIER + KERB

DESIGNED FOR EASY ASSEMBLY, THIS BARRIER IS IDEAL FOR MINIMIZING DAMAGE FROM VEHICLE COLLISIONS WITH LOW-LYING RACKS IN STORAGE AREAS WITH TRANSPORT AND LOADING TRAFFIC. SPECIFICALLY CRAFTED TO PROTECT RACK HEADS FROM CONSTANT IMPACTS, IT REDUCES WEAR AND TEAR CAUSED BY TRANSPORT AND STACKING VEHICLES. REINFORCED WITH A KERB BARRIER, IT OFFERS ENHANCED RESISTANCE AGAINST FORKLIFT FORK IMPACTS AT GROUND LEVEL, ENSURING MAXIMUM DURABILITY AND PROTECTION.

RAYSAN

STRONG AND LIGHTWEIGHT

Thanks to its unique chemical formula, our barrier surpasses steel barriers in both strength and weight. It is significantly lighter while maintaining its exceptional durability.

MODULAR

Thanks to its modular design, our barrier effortlessly adapts to the changing needs of your facility. This flexible solution is extremely easy to install, assemble, disassemble, relocate and organize.

CORROSION-FREE

Unlike steel barriers, our barriers are made of durable polymer materials, making them unaffected by environmental elements such as sunlight and rainwater.

NO PAINTING OR MAINTENANCE REQUIRED

Unlike Raysan's steel barriers that require regular painting and maintenance, our self-colored structure eliminates the need for these processes. Even if the barrier is scratched due to an impact, its surface retains its original color without any change.

UV-RESISTANT

Our barriers are designed with exceptional resistance to UV radiation. Their chemical structure remains intact even after prolonged outdoor use, ensuring long-term durability.


ANTIMICROBIAL


Our barriers have an exceptional chemical formula that prevents them from having any chemical reaction with the substances they come into contact with.

EXPERIENCE UNPARALLELED STRENGTH

WITH OUR ADVANCED POLYMER, CRAFTED
FROM A PREMIUM BLEND OF SOPHISTICATED
POLYOLEFINS AND RUBBER ADDITIVES. THIS
EXCLUSIVE COMPOSITION DELIVERS UNMATCHED
DURABILITY AND FLEXIBILITY. OUR CUTTING-EDGE
ENGINEERING PROCESS REORIENTS THE MOLECULAR
STRUCTURE DURING MANUFACTURING, ENDOWING THE
BARRIER WITH A UNIQUE BUILT-IN MEMORY. THIS
INNOVATIVE FEATURE ENSURES THAT THE BARRIER
RECOVERS COMPLETELY AFTER IMPACTS, MAINTAINING
PEAK PERFORMANCE AND RELIABILITY.







TECHNICAL DRAWING _ D1_ **D2** N 工

FIXING REQUIREMENTS



ELECTROSTATIC PAINT



STAINLESS STEEL



GALVANIZED



Concrete Quality	Minimum C25/30
Concrete Floor Plate Thickness [mm]	Minimum 6"
Water and Humidity	Steel [standart] : Suitable for dry indoor use only. Galvanize : Can be used in most outdoor environments. Stainless Steel : Ideal for outdoor use or environments with frequent exposure to water and humidity.

SUITABLE **APPLICATION**



BUILDING AND EQUIPMENT SAFEGUARDS





DELTA

Post Dimension [D1]

Post Height [H]

235/8"

Rail Dimension [D2]

Ø75/6"

4" x 4"

Rail Length Range [L1]


311/2" - 1041/3"

Barrier Length MAX [L2]

Impact Zone [Z]

1121/5"

95/6"




90° IMPACT DELTA 11,100 JOULE





*90° Impact on Mid Rail of Maximum Post Centres *Results are Reflecting instantaneous Impact Values *Does not Provide Resistance to Sharp Impacts

*Please note that the RAL and PANTONE colours listed



RAYSAN

AS RAYSAN, WE ARE PROUD TO PIONEER THE FUTURE OF INDUSTRIAL SAFETY. WITH OUR STATE—OF—THE—ART FLEXIBLE PROTECTIVE BARRIERS AND SOLUTIONS, WE ARE AT THE FOREFRONT OF INNOVATION, PROTECTING WORKPLACES AROUND THE WORLD. OUR COMMITMENT TO EXCELLENCE AND UNWAVERING DEDICATION TO ADVANCING SAFETY STANDARDS HAS PROPELLED US TO THE TOP OF THE INDUSTRY.

